



USE AND CARE INSTRUCTIONS FOR YOUR NEW FLOOR

*Congratulations on your new
CAP CONCRETE Coating!*

WHEN THE INSTALL IS COMPLETE:

- Do not close the garage door until the morning after install is complete.
- Please allow a minimum of 6-8 hours before walking on, depending upon humidity. Waiting until the next morning is ideal.
- You may drive on the floor 24 hours after install is complete, again depending on humidity. Waiting 36-48 hours is ideal. The floor will reach full chemical resistance at 72 hours of cure time.

ONGOING MAINTENANCE:

- You will be happy to know that your floor is easy to maintain!
- Sweep off sand and salt then simply rinse with water. A squeegee works great to clear water off.
- Ask your dealer about Penntek's LGX-501 floor cleaner. This solvent-based cleaner has been designed specifically to work with Penntek Coatings. When mixed with warm water, the liquid concentrate will make your floors sparkling clean.
- If you prefer, you may use your favorite floor cleaner to manufacturers specifications. We recommend Simple Green, Pine Sol, CLR, and Dawn. Avoid long term exposure to bleach and stay away from acids and highly corrosive materials.
- For tougher cleaning let the cleaner sit on the floor for 5-10 minutes and scrub with a scrub brush or stiff bristle broom, wait an additional five minutes followed by a rinse for a revitalized floor.

